

SEPR-Report EN 13215:2016 E

Model: MC-H8-ZB15KE-PFJ

Refrigerant: R513A Dew Point

S.I.

Item	Symbol	Value (MT)	Unit
Evaporating Temperature	t	-10	°C
Parameters at full load and ambient temperature 32 °C, Subcooling 0.0 K			
Rated Cooling Capacity	Q _A	2.42	kW
Rated Power Input	P _A	1.07	kW
Rated COP	COP _A	2.27	
Parameters at full load and ambient temperature 25 °C, Subcooling 0.0 K			
Cooling Capacity	Q ₂	2.63	kW
Power Input	P ₂	0.95	kW
COP	COP ₂	2.75	
Parameters at full load and ambient temperature 43 °C, Subcooling 0.0 K			
Cooling Capacity	Q ₃	2.07	kW
Power Input	P ₃	1.29	kW
COP	COP ₃	1.61	
Other Items			
Capacity Control		Fixed	
Unit suction line temperature	t11	20.00	°C
Contact Details	Emerson Commercial & Residential Solutions - European Headquarters - Pascalstrasse 65 - 52076 Aachen, Germany Phone: +49 (0) 2408 929 0 - Fax: +49 (0) 2408 929 570 - Internet: climate.emerson.com/en-gb		