

SEPR-Report EN 13215:2016 E

Model: MC-M8-ZB30KE-PFJ

Refrigerant: R448A Arith. Mean Temp.

S.I.

Item	Symbol	Value (MT)	Unit
Evaporating Temperature	t	-10	°C
Annual Electricity Consumption	E	12695	kWh/a
Seasonal Energy Performance Ratio	SEPR	3.46	
Parameters at full load and ambient temperature 32 °C, Subcooling 0.0 K			
Rated Cooling Capacity	Q _A	7.14	kW
Rated Power Input	P _A	3.38	kW
Rated COP	COP _A	2.11	
Parameters at full load and ambient temperature 25 °C, Subcooling 0.0 K			
Declared Cooling Capacity	Q _B	7.86	kW
Declared Power Input	P _B	2.92	kW
Declared COP	COP _B	2.70	
Parameters at full load and ambient temperature 15 °C, Subcooling 0.0 K			
Declared Cooling Capacity	Q _C	8.83	kW
Declared Power Input	P _C	2.37	kW
Declared COP	COP _C	3.72	
Parameters at full load and ambient temperature 5 °C, Subcooling 0.0 K			
Declared Cooling Capacity	Q _D	9.65	kW
Declared Power Input	P _D	1.98	kW
Declared COP	COP _D	4.88	
Parameters at full load and ambient temperature 43 °C, Subcooling 0.0 K			
Declared Cooling Capacity	Q ₃	6.01	kW
Declared Power Input	P ₃	4.27	kW
Declared COP	COP ₃	1.41	
Other Items			
Capacity Control		Fixed	
Degradation Coefficient	Cds	0.25	
Unit suction line temperature	t11	20.00	°C
Contact Details	Emerson Commercial & Residential Solutions - European Headquarters - Pascalstrasse 65 - 52076 Aachen, Germany Phone: +49 (0) 2408 929 0 - Fax: +49 (0) 2408 929 570 - Internet: climate.emerson.com/en-gb		