

## SEPR-Report EN 13215:2016 E

Model: MC-V9-ZB66KE-TFD

Refrigerant: R407A Arith. Mean Temp.

S.I.

Item	Symbol	Value (MT)	Unit
Evaporating Temperature	t	-10	°C
Annual Electricity Consumption	E	26295	kWh/a
Seasonal Energy Performance Ratio	SEPR	3.46	
<b>Parameters at full load and ambient temperature 32 °C, Subcooling 0.0 K</b>			
Rated Cooling Capacity	Q <sub>A</sub>	14.79	kW
Rated Power Input	P <sub>A</sub>	7.04	kW
Rated COP	COP <sub>A</sub>	2.10	
<b>Parameters at full load and ambient temperature 25 °C, Subcooling 0.0 K</b>			
Declared Cooling Capacity	Q <sub>B</sub>	16.47	kW
Declared Power Input	P <sub>B</sub>	6.17	kW
Declared COP	COP <sub>B</sub>	2.67	
<b>Parameters at full load and ambient temperature 15 °C, Subcooling 0.0 K</b>			
Declared Cooling Capacity	Q <sub>C</sub>	18.69	kW
Declared Power Input	P <sub>C</sub>	5.06	kW
Declared COP	COP <sub>C</sub>	3.70	
<b>Parameters at full load and ambient temperature 5 °C, Subcooling 0.0 K</b>			
Declared Cooling Capacity	Q <sub>D</sub>	20.64	kW
Declared Power Input	P <sub>D</sub>	4.13	kW
Declared COP	COP <sub>D</sub>	4.99	
<b>Other Items</b>			
Capacity Control		Fixed	
Degradation Coefficient	C <sub>ds</sub>	0.25	
Unit suction line temperature	t <sub>11</sub>	20.00	°C
Contact Details	Emerson Commercial & Residential Solutions - European Headquarters - Pascalstrasse 65 - 52076 Aachen, Germany Phone: +49 (0) 2408 929 0 - Fax: +49 (0) 2408 929 570 - Internet: <a href="http://climate.emerson.com/en-gb">climate.emerson.com/en-gb</a>		