

SEPR-Report EN 13215:2016 E

Model: R7-2DL-75X

Refrigerant: R407C Arith. Mean Temp.

S.I.

Item	Symbol	Value (MT)	Unit
Evaporating Temperature	t	-10	°C
Annual Electricity Consumption	E	20474	kWh/a
Seasonal Energy Performance Ratio	SEPR	3.30	
Parameters at full load and ambient temperature 32 °C, Subcooling 0.0 K			
Rated Cooling Capacity	Q _A	11.00	kW
Rated Power Input	P _A	4.72	kW
Rated COP	COP _A	2.33	
Parameters at full load and ambient temperature 25 °C, Subcooling 0.0 K			
Declared Cooling Capacity	Q _B	12.26	kW
Declared Power Input	P _B	4.46	kW
Declared COP	COP _B	2.75	
Parameters at full load and ambient temperature 15 °C, Subcooling 0.0 K			
Declared Cooling Capacity	Q _C	14.17	kW
Declared Power Input	P _C	4.03	kW
Declared COP	COP _C	3.52	
Parameters at full load and ambient temperature 5 °C, Subcooling 0.0 K			
Declared Cooling Capacity	Q _D	16.20	kW
Declared Power Input	P _D	3.52	kW
Declared COP	COP _D	4.60	
Parameters at full load and ambient temperature 43 °C, Subcooling 0.0 K			
Declared Cooling Capacity	Q ₃	9.15	kW
Declared Power Input	P ₃	5.09	kW
Declared COP	COP ₃	1.80	
Other Items			
Capacity Control		Fixed	
Degradation Coefficient	Cds	0.25	
Unit suction line temperature	t11	20.00	°C
Contact Details	Emerson Commercial & Residential Solutions - European Headquarters - Pascalstrasse 65 - 52076 Aachen, Germany Phone: +49 (0) 2408 929 0 - Fax: +49 (0) 2408 929 570 - Internet: climate.emerson.com/en-gb		