

## SEPR-Report EN 13215:2016 E

Model: W9-4MT-22X

Refrigerant: R404A Arith. Mean Temp.

S.I.

Item	Symbol	Value (LT)	Unit
Evaporating Temperature	t	-35	°C
Annual Electricity Consumption	E	68159	kWh/a
Seasonal Energy Performance Ratio	SEPR	1.75	
<b>Parameters at full load and ambient temperature 32 °C, Subcooling 0.0 K</b>			
Rated Cooling Capacity	Q <sub>A</sub>	16.03	kW
Rated Power Input	P <sub>A</sub>	12.41	kW
Rated COP	COP <sub>A</sub>	1.29	
<b>Parameters at full load and ambient temperature 25 °C, Subcooling 0.0 K</b>			
Declared Cooling Capacity	Q <sub>B</sub>	18.19	kW
Declared Power Input	P <sub>B</sub>	12.13	kW
Declared COP	COP <sub>B</sub>	1.50	
<b>Parameters at full load and ambient temperature 15 °C, Subcooling 0.0 K</b>			
Declared Cooling Capacity	Q <sub>C</sub>	21.19	kW
Declared Power Input	P <sub>C</sub>	11.53	kW
Declared COP	COP <sub>C</sub>	1.84	
<b>Parameters at full load and ambient temperature 5 °C, Subcooling 0.0 K</b>			
Declared Cooling Capacity	Q <sub>D</sub>	24.08	kW
Declared Power Input	P <sub>D</sub>	10.74	kW
Declared COP	COP <sub>D</sub>	2.24	
<b>Other Items</b>			
Capacity Control		Fixed	
Degradation Coefficient	Cds	0.25	
Unit suction line temperature	t11	20.00	°C
Contact Details	Emerson Commercial & Residential Solutions - European Headquarters - Pascalstrasse 65 - 52076 Aachen, Germany Phone: +49 (0) 2408 929 0 - Fax: +49 (0) 2408 929 570 - Internet: <a href="http://climate.emerson.com/en-gb">climate.emerson.com/en-gb</a>		