

SEPR-Report EN 13215:2016 E

Model: Z9-4MA-22X

Refrigerant: R407F Arith. Mean Temp.

S.I.

Item	Symbol	Value (MT)	Unit
Evaporating Temperature	t	-10	°C
Annual Electricity Consumption	E	62708	kWh/a
Seasonal Energy Performance Ratio	SEPR	3.61	
Parameters at full load and ambient temperature 32 °C, Subcooling 0.0 K			
Rated Cooling Capacity	Q _A	36.80	kW
Rated Power Input	P _A	14.68	kW
Rated COP	COP _A	2.51	
Parameters at full load and ambient temperature 25 °C, Subcooling 0.0 K			
Declared Cooling Capacity	Q _B	40.41	kW
Declared Power Input	P _B	13.60	kW
Declared COP	COP _B	2.97	
Parameters at full load and ambient temperature 15 °C, Subcooling 0.0 K			
Declared Cooling Capacity	Q _C	45.54	kW
Declared Power Input	P _C	11.93	kW
Declared COP	COP _C	3.82	
Parameters at full load and ambient temperature 5 °C, Subcooling 0.0 K			
Declared Cooling Capacity	Q _D	50.65	kW
Declared Power Input	P _D	10.11	kW
Declared COP	COP _D	5.01	
Parameters at full load and ambient temperature 43 °C, Subcooling 0.0 K			
Declared Cooling Capacity	Q ₃	31.11	kW
Declared Power Input	P ₃	16.22	kW
Declared COP	COP ₃	1.92	
Other Items			
Capacity Control		Fixed	
Degradation Coefficient	Cds	0.25	
Unit suction line temperature	t11	20.00	°C
Contact Details	Emerson Commercial & Residential Solutions - European Headquarters - Pascalstrasse 65 - 52076 Aachen, Germany Phone: +49 (0) 2408 929 0 - Fax: +49 (0) 2408 929 570 - Internet: climate.emerson.com/en-gb		