

## SEPR-Report EN 13215:2016 E

Model: ZXME075E-TFD

Refrigerant: R407F Arith. Mean Temp.

S.I.

Item	Symbol	Value (MT)	Unit
Evaporating Temperature	t	-10	°C
Annual Electricity Consumption	E	18535	kWh/a
Seasonal Energy Performance Ratio	SEPR	4.02	
<b>Parameters at full load and ambient temperature 32 °C, Subcooling 0.0 K</b>			
Rated Cooling Capacity	Q <sub>A</sub>	12.12	kW
Rated Power Input	P <sub>A</sub>	4.93	kW
Rated COP	COP <sub>A</sub>	2.46	
<b>Parameters at full load and ambient temperature 25 °C, Subcooling 0.0 K</b>			
Declared Cooling Capacity	Q <sub>B</sub>	13.32	kW
Declared Power Input	P <sub>B</sub>	4.25	kW
Declared COP	COP <sub>B</sub>	3.14	
<b>Parameters at full load and ambient temperature 15 °C, Subcooling 0.0 K</b>			
Declared Cooling Capacity	Q <sub>C</sub>	14.77	kW
Declared Power Input	P <sub>C</sub>	3.45	kW
Declared COP	COP <sub>C</sub>	4.28	
<b>Parameters at full load and ambient temperature 5 °C, Subcooling 0.0 K</b>			
Declared Cooling Capacity	Q <sub>D</sub>	15.75	kW
Declared Power Input	P <sub>D</sub>	2.76	kW
Declared COP	COP <sub>D</sub>	5.70	
<b>Other Items</b>			
Capacity Control		Fixed	
Degradation Coefficient	Cds	0.25	
Unit suction line temperature	t11	20.00	°C
Contact Details	Emerson Commercial & Residential Solutions - European Headquarters - Pascalstrasse 65 - 52076 Aachen, Germany Phone: +49 (0) 2408 929 0 - Fax: +49 (0) 2408 929 570 - Internet: <a href="http://climate.emerson.com/en-gb">climate.emerson.com/en-gb</a>		